

A&G MANUFACTURING CO., INC.

YOUR SOURCE FOR QUALITY, SERVICE AND EFFICIENT BUYING.

PHONE 978-587-2859

WWW.AGMFG.NET

1-888-367-8227

INSULATED METALLIC GROUNDING BUSHINGS WITH ALUMINUM LAY-IN LUG - MALLEABLE IRON

FEATURES

- LINER IS RATED FLAME RETARDANT TO 105°C
- UL LISTED FOR USE WITH COPPER OR ALUMINUM GROUNDING CONDUCTOR

APPLICATION


- INDOOR OR OUTDOOR USE (ALUMINUM LUG)
- USE WITH LOCKNUT TO TERMINATE SERVICE CONDUIT TO A CABINET
- LUG PROVIDED FOR BONDING JUMPER TO A NEUTRAL BUS BAR
- ROUND SURFACE OF BUSHING PREVENTS DAMAGE TO WIRE INSULATION
- PLASTIC LINER PREVENTS DAMAGE TO WIRE INSULATION

STANDARD MATERIAL

- BODY - MALLEABLE IRON
- PLASTIC INSULATOR
- LUG - ALUMINUM
- CLAMPING SCREW - STEEL
- SET SCREWS - STEEL

STANDARD FINISH

- BODY - ZINC PLATED



PART #	UPC#	SIZE	GROUNDING LUG WIRE SIZE		UNIT CARTON	SHIP CASE	WEIGHT CASE	INCHES	
			MIN.	MAX.				A	B
912	10912	1/2"	14	4	50	500	45	1.08	.57
913	10913	3/4"	14	4	50	500	50	1.31	.57
914	10914	1"	14	4	25	250	40	1.61	.65
915	10915	1-1/4"	14	4	20	200	35	1.91	.71
915-1/0	11915	1-1/4"	8	1/0	20	200	35	1.91	.71
916	10916	1-1/2"	14	4	10	100	25	2.16	.73
916-1/0	11916	1-1/2"	8	1/0	10	100	25	2.16	.73
917	10917	2"	14	4	10	100	30	2.72	.73
917-1/0	11917	2"	8	1/0	10	100	30	2.72	.73
918	10918	2-1/2"	8	1/0	---	25	25	3.23	.94
918-3/0	11918	2-1/2"	6	3/0	---	25	25	3.23	.94
919	10919	3"	8	1/0	---	25	18	3.88	.94
919-3/0	11919	3"	6	3/0	---	25	18	3.88	.94
920	10920	3-1/2"	8	1/0	---	10	20	4.43	.94
920-3/0	11920	3-1/2"	6	3/0	---	10	20	4.43	.94
921	10921	4"	8	1/0	---	10	25	4.89	.94
921-3/0	11921	4"	6	3/0	---	10	25	4.89	.941.1
922	10922	5"	6	3/0	---	10	25	6.10	4
923	10923	6"	6	3/0	---	10	35	7.15	1.14

978-587-2859

WWW.AGMFG.NET

1-888-367-8227