

A&G MANUFACTURING CO., INC.

YOUR SOURCE FOR QUALITY, SERVICE AND EFFICIENT BUYING.

PHONE 978-587-2859

WWW.AGMFG.NET

1-888-367-8227

45° LIQUIDTIGHT CONNECTORS WITH INSULATED THROAT - MALLEABLE IRON

FEATURES

- LIQUIDTIGHT, RAIN TIGHT, OIL TIGHT
- SUITABLE FOR WET LOCATIONS
- TAPERED THREADED MALE HUB NPT
- INSULATED THROAT PROTECTS CONDUCTORS FROM ABRASION DAMAGE
- COMPACT SLIM DIAMETER WITH SMALL TURNING RADIUS
- ZINC ELECTRO PLATED FOR EXCELLENT DURABILITY



APPLICATION


- TO SECURE, GROUND AND SEAL LIQUIDTIGHT CONDUIT TO A BOX OR ENCLOSURE
- UL LISTED LIQUIDTIGHT FLEXIBLE METAL CONDUIT FITTINGS ARE SUITABLE FOR USE IN THE FOLLOWING HAZARDOUS LOCATIONS UNDER: NEC 501-4(b), 502-4(a), (2)503-3(a) CLASS 1 DIV.2, CLASS II DIV. 1 AND 2, CLASS III DIV. 1 AND 2 AND ARE SUITABLE FOR GROUNDING IN SIZES 3/8" THROUGH 1-1/2" UNDER NEC 351-1

STANDARD MATERIAL

- MALLEABLE IRON
- STEEL LOCKNUT

STANDARD FINISH

- ZINC PLATED



| PART # | UPC# | CONDUIT SIZE | UNIT CARTON | SHIP CASE | WEIGHT CASE | INCHES | | |
|---------|-------|----------------|-------------|-----------|-------------|--------|------|------|
| | | | | | | A | B | C |
| M45-38 | 80031 | 3/8" - 1/2" KO | 10 | 100 | 24 | 1.18 | 1.39 | 2.51 |
| M45-50 | 80033 | 1/2" | 10 | 100 | 28 | 1.36 | 1.50 | 2.51 |
| M45-75 | 80034 | 3/4" | 10 | 100 | 42 | 1.61 | 1.73 | 2.70 |
| M45-100 | 80024 | 1" | 5 | 50 | 32 | 1.89 | 2.11 | 3.05 |
| M45-125 | 80025 | 1-1/4" | 2 | 20 | 22 | 2.39 | 2.56 | 3.65 |
| M45-150 | 80026 | 1-1/2" | 2 | 20 | 32 | 2.62 | 2.77 | 4.01 |
| M45-200 | 80027 | 2" | 2 | 20 | 49 | 3.24 | 3.38 | 4.64 |
| M45-250 | 80028 | 2-1/2" | --- | 1 | 5 | 3.89 | 4.68 | 6.46 |
| M45-300 | 80029 | 3" | --- | 1 | 7 | 4.74 | 5.33 | 7.01 |
| M45-350 | 80030 | 3-1/2" | --- | 1 | 10 | 5.31 | 5.81 | 7.33 |
| M45-400 | 80032 | 4" | --- | 1 | 12 | 5.82 | 6.42 | 8.20 |

978-587-2859

WWW.AGMFG.NET

1-888-367-8227