

A&G MANUFACTURING CO., INC.

YOUR SOURCE FOR QUALITY, SERVICE AND EFFICIENT BUYING.

PHONE 978-587-2859

WWW.AGMFG.NET

1-888-367-8227

RIGID COUPLINGS TUBULAR THREADED TYPE - STEEL



FEATURES

- NPSM THREAD TYPE

APPLICATION

- INDOOR OR OUTDOOR USE
- USE TO JOIN AND ENSURE PROPER ALIGNMENT OF THREADED RIGID OR IMC CONDUIT

STANDARD MATERIAL

- STEEL




STANDARD FINISH

- ZINC PLATED

APPLICABLE THIRD PARTY STANDARDS

- UL STANDARD: UL 6A
- FED. SPEC: WW-C-563
- NEMA: ANSI C80.1-2015



PART #	UPC#	SIZE	THREADS per inch	SHIP CASE	WEIGHT CASE	INCHES	
						A	B
RGD-C50	20501	1/2"	14	50	7	1.63	1.563
RGD-C75	20502	3/4"	14	50	9	1.64	1.625
RGD-C100	20503	1"	11-1/2	25	10	1.97	2
RGD-C125	20504	1-1/4"	11-1/2	25	10	2.03	2.063
RGD-C150	20505	1-1/2"	11-1/2	25	14	2.06	2.063
RGD-C200	20506	2"	11-1/2	25	25	2.13	2.125
RGD-C250	20507	2-1/2"	8	10	20	2.19	3.125
RGD-C300	20508	3"	8	5	18	3.31	3.25
RGD-C350	20509	3-1/2"	8	5	14	3.41	3.375
RGD-C400	20510	4"	8	4	12	3.52	3.50
RGD-C500	20511	5"	8	2	11	3.95	3.75
RGD-C600	20512	6"	8	1	6	4.25	4

978-587-2859

WWW.AGMFG.NET

1-888-367-8227